

Condition & Repair Hair Masque



Horn Scott Dade

Formulation reference: FM00324/B

Phase	Trade Name	INCI Ingredients	Function	% w/w	Supplier
А	Deionised Water	Aqua	Solvent	Up to 100%	
	Dissolvine NA2	Disodium EDTA	Chelating Agent	0.05	Brenntag
	Citric Acid	Citric Acid	pH Adjuster	0.40	The Soapery
В	Texiterra CS-P	Starch Hydroxypropyltrimonium Chloride	Conditioner	0.30	Scott Bader
С	Monopropylene Glycol USP	Propylene Glycol	Humectant	2.00	OQEMA
	Dehyquart A	Cetrimonium Chloride	Cationic Hair Conditioner	1.50	BASF
D	Lanette 1665	Cetearyl Alcohol	Wax/ Structurant	2.50	BASF
	Ercamuls LF 65 V/FD	Glyceryl Stearate (and) PEG- 100 Stearate	Emulsifier	2.50	OQEMA
	Naissance Argan Oil No. 228	Argania Spinosa Kernel Oi	Oil/ Moisturising	3.00	Naissance
	Lexamine S-13 MB	Stearamidopropyl Dimethylamine	Hair Conditioner	1.50	Inolex
	Texique Lux5	C13-15 Alkane (and) Caprylic/Capric Triglyceride	Natural Emollient	4.00	Scott Bader
	Texiterra Marula Oil	Sclerocarya Birrea (Marula) Seed Oil	Oil/ Moisturising	2.00	Scott Bader

Restore stressed and dry hair with this easy-spreading conditioning masque with nourishing and hydrating ingredients like *Texiterra BF Oryza*, a bioferment antioxidant from black rice, *Texiterra Marula Oil* and a natural silicone alternative, *Texique Lux5*. *Texiterra CS-P* will provide extra conditioning and contribute to soft, nourished and tangle-free hair.













Condition & Repair Hair Masque



HOH	SCU	.t Duuei

Phase	Trade Name	INCI Ingredients	Function	% w/w	Supplier
E	Texiterra BF Oryza	Bacillus / Rice Ferment Filtrate (and) Glycerin (and) Benzyl Alcohol (and) Lactic Acid	Bioferment/ Active/ Antioxidant	3.00	Scott Bader
		Benzyl Alcohol	Preservative	1.00	
		Parfum	Fragrance	QS	

Method

- 1. Weigh out deionised water and add the rest of phase A and mix until dissolved.
- 2. Under fast vortex, slowly add phase B and mix until uniformly dispersed.
- 3. Add phase C to the bulk with mixing between additions and start heating to 70 75°C.
- 4. In a separate vessel combine phase D and heat to 70 75°C.
- 5. At temperature, add heated phase D into the main bulk and homogenise until smooth and uniform.
- 6. Cool down with mixing.
- 7. Below 40°C, add phase E separately and mix until homogenous.

The information in this publication is based on laboratory testing and is believed to be accurate and is given in good faith, but no representation or warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions and are not intended for design purposes. Users are responsible for determining the suitability of these products for their own particular purpose and assume all risk and liability whether used singly or in combination with other materials. No representation or warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties of merchantability, fitness for a particular purpose, non-infringement of any third-party patent or other intellectual property rights.







